

ACCU-CAL™ 50 RADIOMETER

Consistent UV curing requires periodic monitoring of UV intensity or dose. The ACCU-CAL™ 50 radiometer is simple to operate and offers repeatable measurement of UV light. The ACCU-CAL™ 50 can measure UV light emitted from lightguides (3 mm, 5 mm, and 8 mm), UV flood systems, and UV conveyors. With a spectral sensitivity from 320 to 395 nm (UVA), the ACCU-CAL™ 50 measures intensities from 1 mW/cm² to 40 W/cm². A specially designed photo-sensor assembly protects the photo-sensor from the high temperatures sometimes associated with today's high intensity UV spot lamps.

Simple to Operate ✦ **Set Screw Locks Lightguide in Place** ✦ **PTB and NIST Traceable**



ACCU-CAL™ 50 for measuring floods and conveyors only



ACCU-CAL™ 50 for measuring spots, floods, and conveyors

THREE REASONS TO USE A UV RADIOMETER

- ✦ **Maintaining a Light Curing Process** – A radiometer measures whether a light curing system is providing intensity above the “bulb change” intensity. Radiometers provide the same monitoring control for light curing processes that thermometers provide for thermal processes.
- ✦ **Providing a Worker Friendly Light Curing Process** – The ACCU-CAL™ 50 is sufficiently sensitive to measure the intensity of stray or reflected UV light (as little as 1 mW/cm²). DYMAX recommends that worker UVA exposure not exceed 1 mW/cm². For reference, UV (320-395 nm) intensity on a sunny day can range from 2-6 mW/cm².
- ✦ **Measuring Transmission Rates Through Substrates** – A radiometer can be used to measure the transmission rates of various wavelengths through substrates that absorb UV and/or visible light. To assure an effective curing process it is critical to measure the light intensity reaching the resin below the intervening substrate.

SPECIFICATIONS

Spectral Sensitivity	320 to 395 nm
Intensity Range	1 mW/cm ² to 40 W/cm ²
Resolution	Intensity (1 mW/cm ² ; to three significant digits) Dose (1 mJ/cm ²)
Calibration Period	12 months
Operating Temperature Ranges	Optometer: +5 to +40°C Detector: 120°C continuous, Peak 200°C
Measurement Modes	Intensity (mW/cm ² and W/cm ²) Peak Intensity (mW/cm ² and W/cm ²) Dose (J/cm ²)
Light Sources	Lightguides (3 mm, 5 mm, and 8 mm) Floods/Conveyors
Power Supply	Two (2) AA batteries
Battery Life	250 hours (automatic shutoff after 1 hour)
Sensor Dimensions	Photo-Sensor Diameter = 9 mm Diameter = 37 mm Thickness = 8 mm Cable Length = 1 M
Meter Dimensions	120 mm (Length) x 65 mm (Width) x 23 mm (Thickness)

RADIOMETERS and ACCESSORIES

Product	Part Number	Description
ACCU-CAL™ 50 for Flood Lamps and Conveyors	39561	Complete radiometer (without lightguide adapters) Includes storage/carrying case
ACCU-CAL™ 50 for Spot and Flood Lamps and Conveyors	39560	Complete radiometer with lightguide adapters (3 mm, 5 mm, and 8 mm) Includes storage/carrying case
Flood to Spot Adapter Kit	39554	Kit includes three lightguide adapters (3 mm, 5 mm, and 8 mm) and a lightguide simulator*
3 mm Lightguide Adapter	39556	Fits 3 mm ID lightguides (5 mm OD)
5 mm Lightguide Adapter	39557	Fits 5 mm ID lightguides (7 mm OD)
8 mm Lightguide Adapter	39558	Fits 8 mm ID lightguides (10 mm OD)
5 mm Lightguide Simulator	38408	5 mm lightguide simulator with a standard D connection

*A lightguide simulator is used to measure direct spot lamp intensity (required to calculate lightguide transmission)

For further assistance with adhesive and equipment selection, contact your DYMAX Technical Service Representative.

In Europe Call: 0049-69-7165-3568
In North and South America Call: 860-482-1010
In the U.S. Call: 1-877-DYMAX-UV (1-877-396-2988)
In China Call: (86)-519-390-1238
OR Visit DYMAX at www.dymax.com

© 2006 DYMAX Corporation

Please note that most dispensing and curing system applications are unique. DYMAX does not warrant the fitness of the product for the intended application. Any warranty applicable to the product, its application and use is strictly limited to that contained in DYMAX's standard Conditions of Sale. DYMAX recommends that any intended application be evaluated and tested by the user to insure that desired performance criteria are satisfied. DYMAX is willing to assist users in their performance testing and evaluation by offering equipment trial rental and leasing programs to assist in such testing and evaluation. Data sheets are available for valve controllers or pressure pots upon request

LIT159EU 5/17/2006

DYMAX Europe GmbH - Trakehner Strasse 3 - D-60487 Frankfurt am Main - Germany - Phone: 0049-69-7165-3568 - Fax: 0049-69-7165-3830 - E-mail: dymaxinfo@dymax.de - www.dymax.de

DYMAX Corporation - 51 Greenwood Road - Torrington, CT 06790 - Phone: 860-482-1010 - Fax: 860-496-0608 - E-mail: info@dymax.com - www.dymax.com

DYMAX Changzhou High Tech Adhesives Coatings LLC - Building 25, No. 65 XingGang Road, ZhongLou Economic Development Zone, Changzhou, Jiangsu, China 213014 - Phone: (86)-519-390-1238 - Fax: (86)-519-390-1239 - E-mail: simon_ang@dymax.com - www.dymax.cn

DYMAX Asia (HK) - Unit 100610/F., Carnarvon Plaza 20, Carnarvon Road, T.S.T., Kowloon, Hong Kong - Phone: 852-2460-7038 - Fax: 852-2460-7017

DYMAX®, Light-Weld®, Light-Welder®, Multi-Cure®, Ultra Light-Weld®, MEDI-CURE®, MD® and SPEEDMASK® are trademarks of DYMAX Corporation



DYMAX®
Adhesives and Light Curing Systems
www.dymax.com