

New Techspray information for 2009

We have started to integrate into our website some new catalogue sheets from sales partner [Techspray](#). There are seven of them, which you can download here:

- [Conformal Coatings & Temporary Solder Masks](#)
- [Rework & Desoldering Braid](#)

New Techspray information for 2009



TECHSPRAY®

Precision Cleaning Technologies
for the Electronics Industry

PRODUCTION SUPPLIES



Conformal Coatings

RoHS Compliant 

Protect printed circuit boards (PCBs) with Techspray conformal coatings. Coating can either be sprayed and brushed, or boards can be dipped directly into the conformal coating for a thick layer of protection.

- Designed to Protect PCB's
- Can Be Removed for Rework or Repair
- Contain Opti/Scan for UV Inspection

2102 FINE-L-KOTE SR

Silicone Conformal Coating

- UL recognized
- Thermal resistance — to 200°C
- Dielectric strength — 1100 volts/mil
- Moisture resistant
- Chemically resistant
- Vibration resistant — flexible
- IPC-CC-830 & MIL-I-64058C approved

2102-12S 463 mL aerosol
2102-G 3.8 L in metal pail



2108 TURBO-COAT

Acrylic Conformal Coating

- Fastest thermal cure
- Faster throughput without capital investment
- Thick coating — one-pass application
- Fast & easy rework & repair
- Thermal resistance — 125°C
- Dielectric strength — 1000 volts/mil
- IPC-CC-830 & MIL-I-64058C approved
- UL94 V-0 rated

2108-12S 260 mL aerosol
2108-G 3.8 L in metal pail



New Techspray information for 2009

Supplied by:



INTERTRONICS

12a Station Field Industrial Estate, Banbury Road, Kidlington

Oxfordshire England OX5 1JD

t 01865 842842 e info@intertronics.co.uk

Last updated: November 2018

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.