

# Bonding optical couplets

A question from the [DYMAX blog](#):

We have to manufacture a component which is comprised of two individual parts molded from acrylic (PMMA) that have slightly different additives. The parts have concave and convex surfaces which fit onto each other. We want optical coupling between these two surfaces. Can we place one piece as an insert and mold the other over it? Is there some other, better method to achieve the same effect?

One common technique to bond couplets together as described is to mold both acrylic lenses separately and then bond them together with an [optically clear adhesive](#). There are **optical grades** of adhesives that have excellent adhesion to acrylic, are designed to be transparent to most visible wavelengths, possess low shrinkage, stress, and viscosity for easy [dispensing](#) and alignment, and then cure uniformly and evenly under the [proper light source](#). The real benefit is that you can optically align the lenses together while the adhesive is wet, and then cure on-demand.



# Bonding optical couplets

Supplied by:



INTERTRONICS

12a Station Field Industrial Estate, Banbury Road, Kidlington

Oxfordshire England OX5 1JD

t 01865 842842 e [info@intertronics.co.uk](mailto:info@intertronics.co.uk)

Last updated: May 2018

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.