

# Light weight, low density epoxy potting compound is RF transparent

In some applications the weight of potting electronics to protect mechanically or environmentally can be a very significant part of the overall weight of installed equipment – sometimes this can be a problem. We have come up with some very advanced light-weight epoxy potting technology which brings the density right down to 0.6. [IRS 2012 Light Weight Low Density Epoxy Potting Compound](#) is an exciting development for weight critical applications, e.g. in aerospace or autosport, and is potentially of great significance for mainstream automotive systems and even railway systems where it is increasingly recognized that weight saving leads to fuel savings and a reduced carbon footprint.

**IRS 2012** is not only very light on account of its advanced fillers, but is also *very RF transmissive* and is effectively *transparent to radio signals*, with excellent electrical properties, low cure shrinkage, good chemical resistance and good mechanical properties – highly suitable in fact for potting of aerials and related equipment.

The black two-part **IRS 2012** is available in twin pack sachets which may be mixed and transferred to a syringe for precision application if required.

# Light weight, low density epoxy potting compound is RF transparent



Supplied by:

**intertronics**

INTERTRONICS

12a Station Field Industrial Estate, Banbury Road, Kidlington

Oxfordshire England OX5 1JD

t 01865 842842 e [info@intertronics.co.uk](mailto:info@intertronics.co.uk)

# **Light weight, low density epoxy potting compound is RF transparent**

Last updated: May 2018

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.