<u>Araldite 2028-1</u> is a transparent, two-part polyurethane adhesive developed by Huntsman Advanced Materials for the **bonding of a wide range of plastic and metal materials** across a multitude of applications:

- Automotive: Turn signals, brake lights, mirrors
- LED industrial lighting
- **Sport**: Surfboards, equis, recreational boats
- Advertising Sector: Stands, advertising panels, logos, signage
- **Electronics**: Encapsulation of electronic circuits, transformers, sensors
- **General Industry**: Accessories for umbrellas, filters, handicrafts, water meters







**Araldite 2028-1** supersedes the previous version Araldite 2028, benefiting from improvements in UV resistance, shear strength, peel strength and resistance to thermal ageing. The 1:1 mix ratio polyurethane adhesive cures rapidly at room temperature creating a clear bond.

- Open time: 6 minutes at 23 ° C
- Handling strength/Curing time: 30 minutes (to achieve a shear strength greater than 1 MPa)
- Full cure: 8 hours (to achieve a tensile shear strength greater than 10 MPa and a peel strength of 6.6 N/mm)

**Araldite 2028-1** is supplied in cartridges 50 ml with a static mixing nozzle.



<u>Download the ARA 2028-1 Product Data Sheet</u> for more information and visit our <u>Araldite 2000+</u> <u>product page</u> to see other products in the range – we stock these products for next day delivery.

Supplied by:



#### **INTERTRONICS**

12a Station Field Industrial Estate, Banbury Road, Kidlington Oxfordshire England OX5 1JD

t 01865 842842 e <u>info@intertronics.co.uk</u>

Last updated: November 2018

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warrantees expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.