

Best cyanoacrylate adhesive for gap filling

Cyanoacrylate adhesives (CAs) are renowned for being thin, watery liquids. That is their nature. This doesn't help when your bondline is wider than ideal, or varies into larger gaps. In these cases, you will want a CA which has an unusually higher, thicker viscosity – and these do exist.

CAs are now available in a range of different viscosities for gap filling. [Born2Bond Structural](#), [Born2Bond Flex](#) and [Born2Bond Ultra](#) all offer high-viscosity formulations for gap filling. The high viscosity [adhere ADH9454 CA gel](#), for example, prevents running on inclined or vertical surfaces during its 3 to 60 second fixture time, enables gap filling up to 0.5 mm, and minimises the absorption of adhesive into porous substrates to ensure a good bond.

If you're actually filling a hole or carrying out repairs, [Born2Bond Repair](#) is one of our favourite gap-filling cyanoacrylate adhesives. It offers the bonus feature of being quite hard when cured (Shore D 67), and is therefore being machinable, drillable and paintable – within a few minutes. **Born2Bond Repair** is also low shrinkage, helping to ensure that the gaps and holes are filled completely and efficiently. It finds applications in the automotive aftermarket, for example.

Best cyanoacrylate adhesive for gap filling



Cyanoacrylate adhesives (CAs), or “super glues”, have a broad range of applications beyond household repair and basic industrial bonding. This post is part of a blog series in which we highlight our go-to cyanoacrylate adhesives for various jobs. We’d be pleased to offer you advice specific to your application if you [get in touch](#).

Supplied by:

intertronics

INTERTRONICS
12a Station Field Industrial Estate, Banbury Road, Kidlington
Oxfordshire England OX5 1JD
t 01865 842842 e info@intertronics.co.uk

Best cyanoacrylate adhesive for gap filling

Last updated: October 2022

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.