

IJF VD510 Diaphragm Dispensing Valve for Adhesives, CAs, Inks and Low to Medium Viscosity Liquids



Description

The **IJF VD510 Diaphragm Dispensing Valve** is designed for precise flow control of low to medium viscosity liquids. The diaphragm separates the wetted parts from the air supply and therefore it is ideal for dispensing [cyanoacrylates](#), reagents, [UV/light curing adhesives](#), paints, inks, solvents, glues, electrolytes, alcohol and other volatile substances.

Features & Benefits


- Suitable for dispensing low to medium viscosity materials such as acids, adhesives, UV adhesives, solvents, alcohol, cyanoacrylates, reagents, inks, lubricants and more
- Suitable for dispensing hazardous materials
- Stroke adjustment feature provides shot size control allowing for the ability to dispense dots, beads, micro dots, micro beads and for potting/filling
- Minimum shot size 0.001ml
- High cycle rate of 500 shots a minute
- Separated wetted parts
- Ideal for machine integration

The valve is opened by an air pressure pulse supplied by a valve controller (e.g. [FIS DC100 precision dispensing controller](#)). A heavy-duty spring assists the diaphragm to quickly return to its closed state for immediate shut-off. The **IJF VD510** is recommended for high frequency micro shot deposits. Shot

IJF VD510 Diaphragm Dispensing Valve for Adhesives, CAs, Inks and Low to Medium Viscosity Liquids



sizes may be fine tuned by turning an adjustment control at the top of the valve.



Specifications

IJF VD510 Diaphragm Dispensing Valve for Adhesives, CAs, Inks and Low to Medium Viscosity Liquids



Specification	
Operating air pressure	60-90 psi
Maximum fluid pressure	5.0kg/cm ²
Cycle rate	500 cycles per minute
Flow rate	0.3 litres/min
Minimum shot size	0.001ml (material dependent)
Valve weight	76g
Driving part materials	Body: Al (hard coated, black) Piston: SUS303 Piston Seal: natural butyl rubber
Wetted part materials	Valve head: UHMW Polyethylene Diaphragm: UHMW Polyethylene
Connecting ports	Operating air inlet: M5xP0.8 Material inlet: 1/8" NPT Material outlet: luer lock

IJF VD510 Diaphragm Dispensing Valve for Adhesives, CAs, Inks and Low to Medium Viscosity Liquids



Ordering Information

Part number	Description
IJFVD510	Diaphragm valve
IJFVD510-UV	Diaphragm valve – black – fully opaque for light sensitive materials
IJFVD510-SS	Diaphragm valve – stainless steel construction
FISVD510-RK	Diaphragm valve repair kit
FISVD510-UV-RK	Diaphragm valve (black for UV blocking) repair kit
IJFVD510-5	Replacement diaphragm
IJFVD510-5-BLACK	Replacement diaphragm (black) for UV blocking

IJF VD510 Diaphragm Dispensing Valve for Adhesives, CAs, Inks and Low to Medium Viscosity Liquids



Let's start by talking about your application



01865

842842



orders@intertronics.co.uk

- Name*
- Company*
- Phone*
- Email*
- Post code*

If you're in the UK, knowing your postcode would help us get in touch even more quickly. If you're outside the UK, please indicate your country.

IJF VD510 Diaphragm Dispensing Valve for Adhesives, CAs, Inks and Low to Medium Viscosity Liquids



■

■ Tell us about your application

Any information that you submit using this form will be processed according to our [privacy policy](#).

■ Name

This field is for validation purposes and should be left unchanged.

Supplied by:

intertronics

INTERTRONICS

12a Station Field Industrial Estate, Banbury Road, Kidlington

Oxfordshire England OX5 1JD

t 01865 842842 e info@intertronics.co.uk

Last updated: November 2022 Version: 4.4

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.