

TEC 1631a



G3 Flux Remover

Description

The patented cleaning process of **G3 Flux Remover** is non-flammable, and an alternative to other products that contain HCFC-141b or HFE. It is designed specifically for removing R, RA, RMA and SA type flux residues after high temperature reflow. This flux remover can also be used as an all-purpose cleaner to remove light oils, silicones, waxes, greases and other similar contaminants often found in electronics manufacturing.

Techspray launched a new generation of cleaning technologies with their G3 solvents. The patented G3 process is the most innovative in alternative cleaning technologies. These new solvent blends are an excellent replacement for solvents based on flammable alcohols or very expensive HFE's.

Techspray's G3 solvents have excellent cleaning ability, are non-flammable, non ozone depleting, rapidly evaporating, safe on most plastics and have low odour.

Features & Benefits

- Non-flammable
- Effective cleaning
- Non ozone depleting
- Rapidly evaporating
- Safe on most plastics
- Low odour

TEC 1631a

G3 Flux Remover



Ordering Information

Part number	Description
TEC1631a-16S	Flux Remover G3 386ml

Supplied by:

intertronics

INTERTRONICS

12a Station Field Industrial Estate, Banbury Road, Kidlington

Oxfordshire England OX5 1JD

t 01865 842842 e info@intertronics.co.uk

Last updated: July 2019 Version: 6.2

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.