

Potting Industrial LED Beacons IRS 3071

Application

Encapsulating miniature PCB's in various signalling devices for industries including logistics, oil and gas, rail, security, process control and public transport.

Substrates bonded Flame retardant and UV stable ABS

Process Potting and Encapsulation

Pre-treatment None

Curing conditions

- Room temperature cure
- Handling strength in 24 hours
- Full cure in 48 hours

Resistances required

- Flame retardant to UL94 V-0

Key selection criteria

- Long pot life
- Cost effective
- Thermally conductive to 0.5 W/mK
- Non-toxic and RoHS compliant

Customer benefits

- Adds circuits protection at low additional cost
- Thermal conductivity helps manage reliability of components
- Flowable viscosity enables complete coverage, even in hard-to reach areas
- Room temperature cure negates need for curing ovens



Product description

IRS 3071 Polyurethane Potting Compound

is a semi-rigid, room temperature curing, flame retardant and thermally conductive polyurethane potting compound. Specifically designed for the cost-effective encapsulation of a variety of low to medium voltage electrical and electronic applications, the material is medium viscosity, flame retardant to UL94 V-0 at 6mm and has excellent adhesion to a wide range of substrates.

Features and benefits:

- Cost effective
- Thermally conductive for a variety of low to medium voltage applications
- Flame retardant to UL94 V-0 at 6mm
- Medium viscosity
- Resistant to UV, water-based cleaning chemicals, motor oil, lubricants, and most dilute acids and alkalis
- RoHS & WEEE compliant

Suitable in applications involving:

- Electronics potting
- Electronics IP protection
- Thermal management



Let's start by talking about your application

t 01865 842842
e info@intertronics.co.uk
www.intertronics.co.uk

intertronics

Station Field Industrial Estate
Banbury Road, Kidlington
Oxfordshire, England OX5 1JD